
Abrasive paper, self-fastening

PS 33 CK



Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Semi-open
Backing	C-paper

Product benefit

Improved abrasive and stock removal performance thanks to special heat-tempered aluminium oxide abrasive grain - Reduced clogging thanks to sanding active fillers in the size coat and the semi-open coating - Outstanding flexibility paired with good stability and tear resistance thanks to latex impregnated paper backing

Application

Paint/Varnish/Filler	●
Wood	●
Plastic	◑

Applications

- Automotive industry
- Wind energy industry
- Aircraft construction
- Wood processing industry
- Craftsman companies

Available grits:

16 24 30 36 **40** 50 **60** **80** **100** **120** 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Diameter in mm	grain	Hole pattern	type of coat.abras.	Packing unit/pcs.	Cat. number
96	40	GLS 15	PS 33 CK	100	147163
96	60	GLS 15	PS 33 CK	100	147164
96	80	GLS 15	PS 33 CK	100	147165
96	100	GLS 15	PS 33 CK	100	147166
96	120	GLS 15	PS 33 CK	100	148195

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de