Combi non-woven web drum

NCW 600 S



Properties

Bonding agent	Resin
Grain	Aluminium oxide

Application

Stainless steel	●
Metals	●
Plastic	◑

Product benefit

High removal rate and fine surface scratch pattern due to combination of non-woven and abrasive cloth flaps - Long service life

Diameter x Width x Bore in mm	grain	Form	Grade	Colour	Grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 50 x 19	80	⬚	coarse	maroon	aluminium oxide	19 m/s	3700 rpm	3	259896
100 x 50 x 19	100	⬚	medium	maroon	aluminium oxide	19 m/s	3700 rpm	3	259897
100 x 50 x 19	150	⬚	medium	maroon	aluminium oxide	19 m/s	3700 rpm	3	259898
100 x 50 x 19	180	⬚	very fine	maroon	aluminium oxide	19 m/s	3700 rpm	3	259899
100 x 100 x 19	80	⬚	coarse	maroon	aluminium oxide	19 m/s	3700 rpm	1	258905
100 x 100 x 19	100	⬚	medium	maroon	aluminium oxide	19 m/s	3700 rpm	1	258906

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Width x Bore in mm	grain	Form	Grade	Colour	Grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 100 x 19	150		medium	maroon	aluminium oxide	19 m/s	3700 rpm	1	258907
100 x 100 x 19	180		very fine	maroon	aluminium oxide	19 m/s	3700 rpm	1	258908
110 x 100 x 19	80		coarse	maroon	aluminium oxide	19 m/s	3300 rpm	1	320246
110 x 100 x 19	100		medium	maroon	aluminium oxide	19 m/s	3300 rpm	1	320247
110 x 100 x 19	150		medium	maroon	aluminium oxide	19 m/s	3300 rpm	1	320248

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de