
Quick Change Disc

QMC 412



Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Close

Product benefit

For universal use in coarse and intermediate grinding

Application

Metals	●
NF metals	●

Applications

- Apparatus and container manufacturing

Available grits:

16 | 24 | 30 | 36 | 40 | 50 | 60 | 80 | 100 | 120 | 150 | 180 | 220 | 240 | 280 | 320 | 360 | 400 | 500 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | 3000

Diameter in mm	grain	type of coat.abras.	Packing unit/pcs.	Cat. number
38	36	CS 412 Y	100	295174
38	60	CS 412 Y	100	295177
38	80	CS 412 Y	100	295178
38	120	CS 412 Y	100	295180
50	36	CS 412 Y	100	295196
50	40	CS 412 Y	100	295197
50	60	CS 412 Y	100	295199
50	80	CS 412 Y	100	295200

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter in mm	grain	type of coat.abras.	Packing unit/pcs.	Cat. number
50	100	CS 412 Y	100	295201
50	120	CS 412 Y	100	295202
50	180	CS 412 Y	100	295204
50	240	CS 412 Y	100	295205
50	320	CS 310 X	100	295206
76	60	CS 412 Y	50	295221
76	80	CS 412 Y	50	295222
76	120	CS 412 Y	50	295224
76	180	CS 412 Y	50	295226

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de